

Amplify™/MC

High Solids Durable Finish



A high solids UHS floor finish for floors that demand excellent gloss and durability.

Excellent Performance

- ▶ One coat has the gloss of two coats
- ▶ Applies easily and levels perfectly with no mop drag
- ▶ Great mark resistance and durability

Easy-to-Use

- ▶ Install up to five coats in one night
- ▶ Excellent reparability with spray buffing or UHS burnishing
- ▶ Low odor finish is ideal for 24-hour facilities

Designed For

- ▶ Healthcare
 - ▶ Education
 - ▶ Retail
 - ▶ Government
 - ▶ BSC
-



Use Overview

Amplify™ High Solids Durable Finish gives you high-gloss brilliance and durability in fewer coats, saving you time and labor.

Preparation

- ▶ Always barricade area to be finished.
- ▶ Before the first application of **Amplify™ High Solids Durable Finish**, remove all old finish with recommended Diversey stripper.

Coating

- ▶ Apply 3 or more medium coats of **Amplify™ High Solids Durable Finish** with a clean finish mop. Let dry to the touch between coats (about 30 minutes).
- ▶ On porous resilient or stone floors, seal first with 2 coats of recommended Diversey seal.

Maintenance

- ▶ Clean Daily: Dust mop. Then wet clean with recommended Diversey cleaner in an autoscrubber or with a damp mop.
- ▶ Spray buff as needed with recommended Diversey spray buff, a red or beige pad and a 175–1500 RPM machine. Or burnish with a UHS pad and a battery, cord electric or propane machine at 1500–2000+ RPM.
- ▶ Clean and restore gloss with recommended Diversey burnisher. Apply recommended Diversey burnisher using an autoscrubber or damp mop, let floor dry and then burnish.

Recoating

- ▶ Clean thoroughly. Dust mop. Machine scrub with a floor machine or autoscrubber using a blue pad and the recommended Diversey cleaner at the recommended dilution. Rinse well and let dry.
- ▶ Apply 2 new coats of **Amplify™ High Solids Durable Finish**.



Product Specifications

Description	Concentrate
Color/Form	Opaque liquid
Flash Point	> 200°F (> 93.4°C)
pH	7.9–8.5
Scent	Bland
Shelf Life	2 years
Slip Resistance	0.5 minimum (ASTM D2047)
Solids %	25
Solubility	Dispersible
Specific Gravity	1.03

Available Items

Product Code	Description/Package Size	Dilution
5104714	1 x 5 gallon / 18.9 L Envirobox™	Ready-To-Use
4972034	1 x 2.5 L / 2.64 Qt. ProSpeed™ BIB (Bag-in-Box)	Ready-To-Use
4385110	4 x 1 gallon / 3.78 L Containers	Ready-To-Use

Safety Reminder

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS are available on-line at www.diversey.com or by calling 888 352 2249.

Hazard Rating

HMIS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.