



CARPET CARE

Trak-5™

traffic spotter

TECHNICAL DATA SHEET

Packaging Code

4 x 4 L (4 x 1.06 US gal)	1391278002
20 L (5.28 US gal)	1391334001

Description:

A scientifically formulated blend of detergent builders, degreasing solvents, chelating agents, a low foam anionic emulsifier and a deodorant makes TRAK-5 the ultimate traffic spotter and all-purpose spotting agent. Especially effective on heavily soiled rugs and carpets in high traffic and other hard to clean areas. Loosens and breaks up stains caused by oil, tar, lipstick, shoe polish, grease, paint and tracked-in soil, and foods (such as coffee, milk and drinks). Also ideal for use on upholstery.

Use Direction:

NOTE: Pre-test solution for colour fastness on an inconspicuous area of carpet or fabric. Do not dilute product.

PRESOTTING: Use TRAK-5 prior to cleaning with steam and hot water extraction equipment. Using a portable sprayer, spray a fine mist of TRAK-5 over the soiled carpet. Allow 5-10 minutes of contact time, making sure the product does not dry. Proceed to clean.

SPOT AND STAIN REMOVAL: Apply TRAK-5 sparingly with a sprayer or clean cloth. Allow approximately 5 minutes of contact time, then blot off with clean towelling. Do not rub. For stubborn stains, repeat treatment.

ORGANIC INGREDIENTS IN THIS PRODUCT ARE READILY BIODEGRADABLE IN ACCORDANCE WITH OECD 301 STANDARD.

Security:

HEALTH	2
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	X
X =	See SDS
0 =	Insignificant
1 =	Slight
2 =	Moderate
3 =	High
4 =	Extreme

Note:

The data presented herein is based on experiments and information believed reliable. However, we can make no guarantee on performance of, or results obtained through the use of the product herein described owing to varying conditions in laboratories and plants over which we have no control. Neither can any guarantee be given that the products or uses outlined will not infringe any existing patents.

Technical Specifications:

Appearance	Opaque liquid
Colour	Off white
Odour	Floral
Specific Gravity	1.065 – 1.085
pH	12.4 – 13.0
Refractive Index (% Brix)	14.0 – 15.0%



Avmor Ltd.
 950 Michelin, Laval, Québec, Canada H7L 5C1
 Tel.: (450) 629-3800 Fax: (450) 629-4355
 www.avmor.com e-mail: clientservice@avmor.com

**An ISO
 Registered Company**