

TTB 1620 / TTB 1620 T



- 16 gallon solution and recovery tanks
- Fully adjustable flow rate from 0.25 gpm to 1 gpm
- (T) 600 watt traction drive motor moves the unit at speeds up to 4.3 m.p.h.
- LED control panel continuously provides the operator with vacuum, water flow, brush pressure and battery information
- Semi parabolic squeegee with Linatex blades pivots from side to side providing excellent water recovery
- The tear away squeegee is equipped with quick release squeegee blades for easy cleaning
- The onboard charger and 2 x 100 amp hour gel batteries provide 2.5 3.5 hours of run time
- Low voltage shut off prolongs battery life
- The gel batteries are completely maintenance free, emit 1/40 of the hydrogen gas of wet lead acid batteries, are spill proof and can be charged anywhere
- They are the safest, most dependable and longest life batteries on the market.

Specifications

Cleaning path

Pad or Brush Size

Solution / Recovery Tank

Run Time

Brush Motor

Brush Speed

Vacuum Motor

Noise Level

Batteries

Dimensions

TTB 1620

20"

20"

16 Gallon

2.5 - 3.5 Hours

400 Watt

100 rpm

400 Watt

65 dBa.

2 x 100 ah gel batteries

57 x 21 x 43 (LxWxH)

TTB 1620 T

Traction Motor

250 Watts

Traction Speed

0 - 4.3 mph

Max Gradient

11 Degrees

Water Flow Rates

.25 - 1 gpm.



1205 Britannia Road East, Mississauga, Ontario, L4W 1C7

1.800.387.3210 TOLL-FREE 1.800.709.2896 FAX www.nacecare.com