



Eko-Shine*

Technical Data Sheet #8760

Powerful concentrated floor stripper

Eko-Shine* floor finish resists daily wear caused by traffic, dirt and black shoe marks. Eko-Shine combines the characteristics of a floor sealer with those of a floor finish. Versatile, this floor finish can be polished with a low speed floor machine as well as with an ultra high speed floor machine to increase gloss.

Advantages

- High brilliance
- Resist daily wear

Physical and chemical properties

Appearance	White liquid
Odor	Unscented
Viscosity (25 °C)	< 10 cPs
pH (25 °C)	7.2 - 8.8
Solubility	Water soluble
Specific gravity (25 °C)	1.015 - 1.035
Flammability	Nonflammable
Stability	Stable between 10 °C and 40 °C
Storage	Avoid frost and excessive heat
Biodegradability	Readily biodegradable
Percent non-volatile solids	25 %




EkoLogik® Available formats



4L



20L



PRODUCT CERTIFIED FOR REDUCED ENVIRONMENTAL IMPACT. VIEW SPECIFIC ATTRIBUTES EVALUATED: UL.COM/EL UL 2777

CERTIFICATE OF COMPLIANCE



Lalema Inc.

EKO-SHINE, Fini à plancher

UL 2777 - 2011 Standard for the Sustainability for Hard Floor Care Products
Standard

ECP 07089
Project Number

38004-4270
Certificate Number

01/30/2008 - 07/23/2018
Certificate Period



Environment