



Eko-Strip*

Technical Data Sheet #3100

Powerful concentrated floor stripper

Eko-Strip* is a floor stripper that removes wax and floor finish with the help of a dual speed floor machine and floor pads for stripping. This floor stripper will effectively strip build-up of multiple coats, water emulsion seals and long aged and/or over spray-buffed films on all types of floor.

Advantages

- Easily removes accumulations of floor finish
- Effective in cold water
- No odor

Physical and chemical properties

Appearance	Light yellow liquid
Odor	Unscented
Viscosity (25 °C)	< 10 cPs
pH (25 °C)	10.7 - 12.8
Solubility	Water soluble
Specific gravity (25 °C)	1.010 - 1.020
Flammability	Nonflammable
Stability	Stable between 10 °C and 40 °C
Storage	Avoid frost and excessive heat
Biodegradability	Readily biodegradable



Dilution rates

Léger / Light (1:30)

5.4 oz / gal †
34 mL / L †



Fort / Strong (1:10)

16 oz / gal †
100 mL / L †


Moyen / Medium (1:20)

8 oz / gal †
50 mL / L †

*Procéder d'abord à un essai.
Always test first.*

*† d'eau tiède ou froide
† of warm or cold water*

EkoLogik® Available formats



PRODUIT CERTIFIÉ À IMPACT ENVIRONNEMENTAL RÉDUIT.
Veuillez consulter les attributs spécifiques évalués: UL.COM/EL
UL 2777

PRODUCT CERTIFIED FOR REDUCED ENVIRONMENTAL IMPACT. VIEW SPECIFIC ATTRIBUTES EVALUATED: UL.COM/EL
UL 2777

CERTIFICATE OF COMPLIANCE



Lalema Inc.

EKO-STRIP, Décapant à plancher concentré puissant

UL 2777 - 2011 Standard for the Sustainability for Hard Floor Care Products
Standard

ECP 07089
Project Number

38005-4270
Certificate Number

01/30/2008 - 07/23/2018
Certificate Period



Environment