

Floor Sealer

Code: FS23



Safeblend 23 Floor Sealer is specially formulated as an excellent base for a variety of floor surfaces including linoleum and terrazzo. It is water, powdering and slip resistant. Safeblend 23 Acrylic Floor Sealer adds extra gloss to subsequent coats of floor finishes. Environmentally preferable, contains no zinc or heavy metals.

DIRECTIONS FOR USE: Preparation: Blockade area until floor is dry as floors will be very slippery when wet. Strip floor thoroughly using a SAFEBLEND stripper. Pick up stripped finish before it dries using a wet vacuum, a clean mop or autoscrubber. Rinse with liberal amounts of cold clean water until all residues have been eliminated. Allow floor to dry completely before applying Safeblend 23 Sealer. Application: For best results, use a clean floor finish mop and clean bucket (or use liner in bucket) and wringer. Pour sealer into bucket. Saturate mop with Safeblend 23 Sealer. Press mop firmly into wringer to remove excess product but do not wring mop. Apply Safeblend 23 Sealer in even coats. Apply two coats. Allow each coat to dry. Drying time is approximately 30 minutes. (Drying time may vary depending on temperature, humidity, ventilation and thickness of each coat). Since Safeblend Sealer is a semi-permanent sealer, we recommend that any one of our floor finishes be used as a final top coat such as Safeblend Floor Finish

NOTE: Do not pour unused floor finish back into container. Do not let product spoil food, feed or potable water during use. Do not use on food contact surfaces. The amount of product used should not be in excess of that required to achieve its intended technical effect. STORAGE: Keep in a tightly sealed container in a well-ventilated room. Do not store on surfaces that may come into contact with food products. Keep from freezing.

| | $\overline{}$ |
|---|---------------|
| PHYSICAL PROPERTIES | |
| Boiling Point: 100°C | |
| Specific Gravity (H2O =1): 1.01 at 20°C | |
| % Volatile (w/w): Approx. 90 | |
| Solubility in Water: Complete | |
| pH (as supplied): 8-9 | |
| Physical State: Liquid | |
| Viscosity: < 100 cps at 25°C | |
| Flash point : < 93°C | |
| Appearance and Odour: White liquid, characteristic odor | |

GHS: skin irritant category 2 and an eye irritant category 2

CFIA: Not regulated

Brix Solids (%): 23

% Non-Volatile solids: 16

Toxicity: Non-toxic to humans and animals

(LD50 > 5,000/KG).

Non-toxic to aquatic life using recommended

dilutions (IC50 ≥10MG/L)



EcoLogo Certified

UL 2777

| Non - Toxic | ~ | No APE's, NPE's, NTA or EDTA | < | All of our containers are fully recyclable | V |
|-------------------------------|----------|---|----------|---|---|
| Biodegradable OECD 301 | ~ | No Carcinogens | \ | Our boxed contain at least 50% recycled fibre | ~ |
| Non-Corrosive to eyes or skin | ~ | Not regulated by Transport of Dangerous | (| Our 4L bottles are made with at least 25% | |
| Inorganic phosphate-free | ~ | Goods Regulation (TDG) | Ľ | post-consumer waste | _ |
| No ammonia | ~ | Concentrates effective when diluting with cold water | | Our labels use FDA approved vegetable based ink | |
| No bleach | V | Reduce, Re-use. Recycle | < | vegetable based ink | _ |















