

# RESISTOL 18

## Floor Finish

---

### DESCRIPTION:

This high-quality Floor Finish is specially formulated to provide a durable, high-gloss floor finish after every job. It excels in durability and black heel scuffs, slip and powdering resistance. The natural colours of all floor surfaces are enhanced by RESISTOL floor care products. To obtain a "wet-look" appearance, use a high-speed buffing machine with.

**18% SOLIDS – ULTRA HIGHT GLOSS, BUFFABLE, EXTRA DURABLE,SLIP**

---

### DIRECTIONS:

FOR BEST RESULTS: Follow these procedures:

STRIPPING: Remove all previous coatings with RESISTOL STRIPPER. Rinse well with water.

APPLICATION: Apply even coats of RESISTOL 18 floor finish with a clean damp mop. Allow proper drying time between coats according to ventilation and room temperature.

MAINTENANCE: Clean with RESISTOL ND-50 Neutral Detergent.

IMPORTANT: Do not pour unused materials into the original container.

NOTE: Surfaces subject to direct food contact must be thoroughly rinsed with potable water.

---

### PHYSICAL PROPERTIES:

Boiling Point	100 °C
Specific Gravity	(H <sub>2</sub> O = 1): 1.018 at 20° C
Vapor Pressure	(mm Hg): N/A
% Volatile	(Wt %): 75 - 80
Vapor Density	(Air = 1): N/A
Evaporation Rate	(Water = 1): 1
Solubility in Water	Dispersible
pH (as supplied)	8.5 - 9.0
Physical State	Liquid
Viscosity	< 1000 cps at 25° C
Appearance and Odor	White liquid
Odour	Acrylic odor
Odor Threshold (ppm)	n/a

---

**TDG CLASSIFICATION:** Not regulated

---

**GHS:** skin irritant category 2 and an eye irritant category 2

---

**STORAGE:** Keep in a tightly sealed container, in a well-ventilated room at room temperature. Keep from freezing.

---