



# TECHNICAL DATA SHEET

## ZERO - Floor Finish

High Gloss Retention, Durable and No Maintenance Required Code: REZE



Resistol Zero is formulated to offer maximum durability requiring low or no maintenance. The natural colours of all floor surfaces are enhanced by RESISTOL floor care products.

### DIRECTIONS FOR USE:

**Preparation:** Blockade area until floor finish is dry as floors will be very slippery during the preparation and application of the finish. Scrub or strip floor thoroughly using CHEMOTEC or SAFEBLEND brand products. Pick up stripped finish before it dries using a wet vacuum, a clean mop or autoscrubber. Rinse with liberal amounts of cold clean water until all residues have been eliminated. Allow floor to dry completely before applying RESISTOL ZERO Floor Finish. **Application:** For best results, use a clean floor finish mop and clean bucket (or use liner in bucket) and wringer. Pour floor finish into bucket, saturate mop with RESISTOL ZERO Floor Finish. Press mop firmly into wringer to remove excess product but do not wring mop. Apply RESISTOL ZERO Floor Finish in even coats. Allow each coat to dry. Drying time is approximately 30 minutes. (Drying time may vary depending on temperature, humidity, ventilation and thickness of each coat). Apply 3 - 4 coats or until desired gloss is achieved. Never apply more than 4 coats per 24-hour period.

**Coverage:** Approximately 2000 square feet per 4 litres. **Cleaning:** Dust mop. Clean floor as needed using a CHEMOTEC or SAFEBLEND neutral cleaner.

**NOTE:** Do not pour unused floor finish back into container. Do not let product spoil food, feed or potable water during use. Do not use on food contact surfaces. The amount of product used should not be in excess of that required to achieve its intended technical effect.

**STORAGE:** Keep in a tightly sealed container in a well-ventilated room. Do not store on surfaces that may come into contact with food products. Keep from freezing.

|   |   |
|---|---|
| <b>PHYSICAL PROPERTIES</b>                                      | <b>GHS:</b> skin irritant category 2 and an eye irritant category 2 |
| <b>Boiling Point:</b> 100°C                                     | <b>CFIA:</b> Accepted   |
| <b>Specific Gravity (H<sub>2</sub>O =1):</b> 1.02 at 20°C       | <b>Vapor pressure: (mm Hg):</b> N/A                                 |
| <b>% Non-volatile solids</b> 21 <b>% Brix Solids:</b> 23        | <b>Vapor Density: (Air=1):</b> N/A                                  |
| <b>Solubility in Water:</b> Miscible                            | <b>Evaporation Rate: (Water = 1):</b> 1                             |
| <b>pH (as supplied):</b> 8-7                                    | <b>Flash point:</b> > 93°C  |
| <b>Odour Threshold (ppm):</b> N/A                               | <b>TDG Classification:</b> Not regulated                            |
| <b>Appearance and Odour:</b> White liquid, characteristic odour | <b>Physical State:</b> Liquid                                       |
|   | <b>Viscosity:</b> < 100 cps at 25°C                                 |
|   | <b>Slip Coefficient:</b> > 0.5 (ASTM D 2047)                        |

### Please Recycle

|   |
|---|
| ● All of our containers are fully recyclable      |
| ● Our boxes contain at least 50% recycled fibre   |
| ● Our labels use FDA approved vegetable based ink |



8820, Place Ray Lawson, Anjou, Québec, Canada H1J 1Z2  
Tel 514.729.6321 • 800.729.6321  
Fax 514.729.6322  
service@safblend.com www.safblend.com

For more information, please visit  
[www.chemotec.ca](http://www.chemotec.ca)

