TECHNICAL DATA SHEET RESISTOL GEL





Resistol GEL Stripper is specially formulated to quickly and effectively remove heavy build up of floor finish from vertical surfaces such as baseboards and corners. Rinsing is easily accomplished.

DIRECTIONS FOR USE:

For best results, apply a uniform thick coating to baseboards being stripped by means of a clean paint brush. Allow sufficient time for stripper to work, usually 5-10 minutes, longer if temperature is low or in case of thick buildup. Performance improves as temperature increases. Scrub with a swivel utility stripping pad to aid in removal of the finish. Repeat if necessary. Removal: Use a mop to remove bulk of loosened floor finish and stripper followed by a clean water rinse until all residues are removed. NOTE: The amount of product used should not be in excess of that required to achieve its intended technical effect. Do not let product spoil food, feed or potable water during use. Do not use on food contact surfaces.

STORAGE: Keep in a tightly sealed container in a well-ventilated room. Do not store on surfaces that may come into contact with food products. Keep from freezing.

PHYSICAL PROPERTIES Boiling Point: 100°C	GHS: Skin Corrosion/Irritation — category 1; Serious eye damage/eye irritation — category 2	
Specific Gravity (H ₂ O =1): 1.02 at 20°C	CFIA: Accepted	
% Volatile (Wt%): Approx. 90	Vapor pressure: (mm Hg): 20	
Solubility in Water: Complete	Vapor Density: (Air=1): N/A Evaporation Rate: (Water = 1): approx 1	
pH (as supplied): Approx. 12		
Odour Threshold (ppm) : N/A Flash point: None		
Appearance and Odour: Clear yellow liquid, lemon odour	TDG Classification: Not regulated	
	Physical State: Liquid	
	Viscosity: approx 2,000 cps at 20°C	

Please Recycle

All of our containers are fully recyclable	
Our boxes contain at least 50% recycled fibre	
Our labels use FDA approved vegetable based ink	



