

# EP85 Sidekick™ restorer

## TECHNICAL DATA SHEET

**Packaging Code**  
4 x 4 L (4 x 1.06 US gal) 2302278001

**Description:**

EP85 SIDEKICK is a versatile, low odour restorer designed with the newest in environmentally preferable polymer technology. It can be mopped on or applied with an autoscrubber. EP85 SIDEKICK is compatible with all Avmor floor finishes and it will accommodate both low and high maintenance schedules. EP85 SIDEKICK will restore gloss and prolong the life of the floor finish. Excellent for vinyl composition, linoleum, sheet vinyl, concrete, terrazzo, quarry, Mexican tile and most resilient type flooring.

- Zinc free
- No APE's
- Low VOC's
- No Formaldehyde
- Low Odour
- No butyl
- No EDTA / NTA
- Organic ingredients in this product are biodegradable in accordance with OECD standard.

Application	Dilution
Autoburnish	1:11-19
Mop on	1:6
Spray buff	1:4

**Use Directions:**

**AUTOBURNISH RESTORER:** Add 1 part EP85 SIDEKICK to 11-19 parts water (50-85 ml per 1 L solution). **For lightly soiled floors:** 1. Dust mop entire floor with a clean dust mop. 2. Scrub and pick-up EP85 SIDEKICK in one operation. 3. Burnish floor for high shine. 4. Dust mop floor once again. **For heavily soiled floors:** 1. Dust mop entire floor with a clean dust mop. 2. Prescrub with neutral cleaner and allow solution to work on floor for 3-5 minutes. Pick-up dirty solution with a wet/dry pick-up vacuum. 3. Scrub with EP85 SIDEKICK and pick-up solution. 4. Burnish for high shine.

**MOP ON RESTORER:** Add 1 part EP85 SIDEKICK to 6 parts water. 1. Dust mop entire floor with a clean dust mop. 2. Apply ready-to-use solution with a clean finish mop. Allow to dry, then burnish surface to a high lustrous shine. 3. Dust mop once again. **NOTE:** For heavily soiled areas top scrub floor with a floor machine and neutral cleaner. Pick up before applying restorer and burnishing.

**SPRAY BUFF RESTORER:** Add 1 part EP85 SIDEKICK to 4 parts water. 1. Dust mop entire floor with a clean dust mop. 2. Spray a fine mist of EP85 SIDEKICK on the floor. Do not overwet. 3. Buff misty area immediately with proper floor pad. 4. Dust mop area once again if necessary. **NOTE:** For heavily soiled areas, top scrub floor with a floor machine and neutral cleaner and pick-up before applying spray buff system.

**RECYCLING:** This product package including the container, label, and shipping carton are all designed to be recycled. Follow all Federal, Provincial and Local regulations regarding waste disposal.

For additional information, please visit [www.avmor.com](http://www.avmor.com)

**Security:**

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	X
X =	See MSDS
0 =	Insignificant
1 =	Slight
2 =	Moderate
3 =	High
4 =	Extreme

**Note:**

The data presented herein is based on experiments and information believed reliable. However, we can make no guarantee on performance of, or results obtained through the use of the product herein described owing to varying conditions in laboratories and plants over which we have no control. Neither can any guarantee be given that the products or uses outlined will not infringe any existing patents.

**Technical Specifications:**

Appearance	Opaque liquid
Colour	White
Odour	Acrylic
Specific Gravity	1.020 – 1.040
pH	7.4 – 8.4
Refractive index (% Brix)	21.0 – 23.0%

