

EP86 Lokseal™

floor sealer

TECHNICAL DATA SHEET

Packaging Code

4 x 4 L (4 x 1.06 US gal)	2321278001
20 L (5.28 US gal)	2321334001

Description:

EP86 LOKSEAL Floor Sealer is designed with the newest in environmentally preferable polymer technologies. EP86 LOKSEAL is compatible with all Avmor floor finishes. It is highly recommended for sealing pores and leveling floor surfaces in preparation of floor finish application. Excellent for vinyl composition, linoleum, sheet vinyl, concrete, terrazzo, quarry, Mexican tile and most resilient type flooring.

- Formaldehyde Free.
- Metal Free.
- APE Free.
- Low VOC's.
- Low Odour.
- Organic ingredients in this product are readily biodegradable in accordance with OECD 301 standard.

Use Directions:

1. Thoroughly strip floor, removing old floor finish.
2. Rinse with clean water and let dry.
3. Apply 1-2 coats of EP86 LOKSEAL.
4. Allow 30 minutes between coats.
5. After sealing, apply Avmor floor finish.

RECYCLING: This product package including the container, label, and shipping carton are all designed to be recycled. Follow all Federal, Provincial and Local regulations regarding waste disposal.

Precautions for food plants:

Must be applied in keeping with manufacturers' recommendations for application on hard smooth level surfaces. To avert possible adverse organoleptic effects in food, which are processed in the area, adequate precautions should be taken to ensure that the volatile constituents of the applied products do not contaminate the foods.

For additional information, please visit www.avmor.com

Security:

HEALTH	0
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	X
X =	See SDS
0 =	Insignificant
1 =	Slight
2 =	Moderate
3 =	High
4 =	Extreme

Note:

The data presented herein is based on experiments and information believed reliable. However, we can make no guarantee on performance of, or results obtained through the use of the product herein described owing to varying conditions in laboratories and plants over which we have no control. Neither can any guarantee be given that the products or uses outlined will not infringe any existing patents.

Technical Specifications:

Appearance	Opaque liquid
Colour	White
Odour	Acrylic
Specific Gravity	1.000 – 1.020
pH	8.0 – 8.5
Refractive Index (% Brix)	16,0 – 20,0%
Coverage	400 square meters/4 liters

