



**WASHROOM CARE**

# Bo-Lav™

## liquid bowl and urinal cleaner

# TECHNICAL DATA SHEET

**Packaging Code**

12 x 909 ml (12 x 30.7 fl. oz) 1375206003  
 4 x 4 L (4 x 1.06 US gal) 1375278001

**Description:**

BO-LAV is a blend of acid and surfactant working in concert to remove hard mineral deposits through chemical action. Heavy duty. Ideally made for weekly use to remove stains and other soil from porcelain urinals and toilet bowls.

**Use Directions:**

TO CLEAN BOWLS: Holding mop over bowl, pour 115 ml of bowl cleaner into bowl water and swab entire bowl. Allow to act for 5 minutes. Flush toilet and rinse out mop. DO NOT USE ON SINKS, BATHTUBS OR ANY ENAMELLED SURFACES. Harmless to plumbing and septic tanks.

TO CLEAN URINALS: Remove screen or strainer. Saturate bowl mop with bowl cleaner and wet entire surface. Pour 115 ml around outlet and into drain opening. Allow to act 5 minutes. Next swab all urinal surfaces and openings until clean and deodorized. Replace screen or strainer and flush unit. Rinse out mop.

**Precautions for food plants:**

For non-food contact surfaces only. Avoid contamination of food during use. Do not store in food processing or food storage area.

**Security:**

HEALTH	3
FLAMMABILITY	0
REACTIVITY	1
PERSONAL PROTECTION	X
X =	See SDS
0 =	Insignificant
1 =	Slight
2 =	Moderate
3 =	High
4 =	Extreme

**Note:**

The data presented herein is based on experiments and information believed reliable. However, we can make no guarantee on performance of, or results obtained through the use of the product herein described owing to varying conditions in laboratories and plants over which we have no control. Neither can any guarantee be given that the products or uses outlined will not infringe any existing patents.

**Technical Specifications:**

Appearance	Opaque liquid
Colour	Green to Blue-Gray
Odour	Methyl salicylate
Specific Gravity	1.090 – 1.140
pH	1.0 – 2.0
Refractive Index (% Brix)	34.0 – 36.0%



Avmor Ltd.  
 950 Michelin, Laval, Québec, Canada H7L 5C1  
 Tel.: (450) 629-3800 Fax: (450) 629-4355  
 www.avmor.com e-mail: clientservice@avmor.com

An ISO  
 Registered Company