

COMMERCIAL HAND DRYER

CAST IRON CONSTRUCTION FOR COMPACT, STYLISH DESIGN WITH FAST DRYING SPEED AND LONG LASTING DURABILITY.


ENVIRONMENTALLY FRIENDLY, USING LESS THAN 1/6th OF THE ENERGY OF A CONVENTIONAL HAND DRYER


FEATURES

- Powerful
- Stylish appearance
- Efficient, fast and safe
- Automatic Sensor
- Suitable to be installed in high traffic places
- 3 years warranty
- Small footprint
- Vandal proof
- Heavy duty reinforced steel
- Tamperproof screws

DIMENSIONS

FRONT VIEW





APPLICATIONS

- Washrooms and clean up areas, commercial facilities, factories, restaurants and hospitals
- High traffic areas
- Ideal for pools, gyms, stadiums (hair drying enable)



SIDE VIEW

DISTANCE FROM BOTTOM EDGE OF DRYER TO FLOOR

Men	47" (119 cm)		
Women	44" (112 cm)		
Children 8-10 years	35" (89 cm)		
Children 11-13 years	38" (97 cm)		
Children 14-16 years	44" (112 cm)		
Disabled	36" (91 cm)		



SPECIFICATIONS

Operation Voltage 110 - 120 Vac, 50 - 60 Hz, 2.0 - 2.4 KW 220 - 240Vac, 50 - 60Hz, 2.0 - 2.4 KW

Warm Air Speed Output 28 m/s (62.6 miihr)

Drier Shall Deliver 345 rrilh (202 CFM)

Motor Type 200 W, 5,500 R.P.M., brush motor

Motor Thermal Protection Auto resetting thermostat

Heater Thermal Protection Auto resetting thermostat

turn units off at 65°C (14°F);

Thermal fuse cut unit off at 141°C (28°F)

Drying Time Approximately 20–25 seconds

Sound Level 70±3 dB @ 1 m

turns unit off at 105°C (221°F)

Timing Protection 60 seconds auto shut off

Drip Proof IPX1

Isolation Class 1

Material Steel

Cover Finish Porcelain Enameled Coating

Dimensions 281 mm (W) x 247 mm (H) x 212 mm (D)

 $[11-1/16" (W) \times 9-23/32" (H) \times 8-11/32" (D)]$

ORDERING GUIDE

	Model No.	Colour	Watts	Volts Hz	Air Velocity LFM	Air Volume CFM	Noise dB	Dimensions (W x H x D) (mm/in.)	Weight (kg/lbs.)
_	-HK-2400PS/240	White	2200	110-120, 220-240	16000	202	70	281X247X212 (11X9X8)	6.8/15
C	-HK-2400MA/240	Chrome	2200	110-120, 220-240	16000	202	70	281X247X212 (11X9X8)	6.8/15













