



FLOOR CARE

Distance TM

sealer finish

Packaging Code

4 x 4 L (4 x 1.06 US gal) 2390278001 20 L (5.28 US gal) 2390334001 210L (55.48 US gal) 2390390001

Description:

DISTANCE is a crystal clear, high gloss sealer finish with superior dirt and black mark resistance. This versatile floor sealer is ideal for both hard and resilient floors. DISTANCE responds well to varying maintenance schedules.

Use Directions:

- 1) Mix DISTANCE according to dilution chart.
- 2) Thoroughly clean the floor prior to applying DISTANCE.

Applying as a sealer or finish:

- 1) On a stripped floor, apply 3 to 5 coats of DISTANCE with a clean mop or wax applicator.
- 2) Allow each coat to dry completely, normally 30 minutes before recoating.
- 3) Apply additional coats depending on gloss expectations and traffic conditions.

Dilution chart:

Use as a Floor Finish: Use DISTANCE undiluted for a high performance floor finish. Use as a Sealer Finish: Use DISTANCE undiluted to make a high performance floor sealer.

Security:

HEALIH	
FLAMMABILITY	(
REACTIVITY	(
PERSONAL PRO	TECTION 2
X =	See SDS
0 =	Insignifican
1 =	Sligh
2 =	Moderate
3 =	Higl
4 =	Extreme

Note:

The data presented herein is based on experiments and information believed reliable. However, we can make no guarantee on performance of, or results obtained through the use of the product herein described owing to varying conditions in laboratories and plants over which we have no control. Neither can any guarantee be given that the products or uses outlined will not infringe any existing patents.

Precautions for food plants:

Must be applied in keeping with manufacturers' recommendations for application on hard smooth level surfaces. To avert possible adverse organoleptic effects in food, which are processed in the area, adequate precautions should be taken to ensure that the volatile constituents of the applied products do not contaminate the foods.

Technical Specifications:

Appearance	Opaque liquid
Colour	White
Odour	Acrylic
Specific Gravity	1.008 – 1.048
рН	7.0 – 9.5
Refractive index (% Brix)	24.0 – 27.0%
Coverage	200 square meters/4 liters

Avmor Ltd.

950 Michelin, Laval, Québec, Canada H7L 5C1 Tel.: (450) 629-3800 Fax: (450) 629-4355 www.avmor.com e-mail: clientservice@avmor.com

An ISO **Registered Company**