

Over & Under® Sealer



A comprehensive floor care solution for all finishes used on resilient flooring.

Enhances the Appearance of Your Floors

- ▶ Penetrates, seals and protects to extend the life of new and older flooring
- ▶ Improves performance of floor finishes by providing better adhesion, leveling and enhances gloss of all Diversey floor finishes

Easy-To-Use

- ▶ Easily removed with all Diversey strippers
- ▶ Non-solventated, suitable for use on a wide range of flooring

Designed For

- ▶ Education
 - ▶ Retail
 - ▶ Government
 - ▶ BSC
-



Use Overview

Over & Under® Sealer is a crystal clear water-based acrylic sealer for resilient floors. Use it for resilient flooring such as vinyl, vinyl composition, vinyl asbestos, rubber, linoleum and asphalt tile.



Applying Floor Sealer

- ▶ Clean or strip floor using Diversey brand stripper according to label directions.
- ▶ Apply one coat of **Over & Under® Sealer** using a clean mop or TrailBlazer™/MC Floor Finish Applicator.
- ▶ Allow 30 minutes drying time between coats.
- ▶ After a minimum of 2 coats of **Over & Under® Sealer**, top coat with 2–3 coats of a recommended Diversey floor finish according to label directions.

Maintenance

- ▶ Dust mop or sweep the floor as necessary.
- ▶ Clean floor with appropriate Diversey brand cleaner according to label directions.
- ▶ Maintain the finish gloss using periodic recoating, spray buffing or burnishing according to finish label.

Precautions

- ▶ Do not dilute.
- ▶ Always test **Over & Under® Sealer** on a small area of the floor to be finished before finishing the entire floor.
- ▶ Intended for interior surfaces only.
- ▶ Do not apply to exterior or vertical surfaces, or use on wood, cork and concrete floors.
- ▶ Will not adhere to floors previously finished with a paste wax, paste wax must be removed by a thorough stripping before sealer can be applied.
- ▶ Do not use on surfaces colder than 45° F (7° C).
- ▶ Do not return unused product to original container.
- ▶ Floors can become slippery when wet, clean up spills promptly.
- ▶ Keep from freezing.

Product Specifications

Description	
Color/Form	Opaque off-white liquid
Flash Point	>200° F (>93.4° C)
pH	8.3
Scent	Ammonia
Shelf Life	2 years
Slip Resistance	0.5 minimum (ASTM D2047-82)
Solids %	18
Solubility	Dispersible
Specific Gravity	1.03

Available Items

Product Code	Description/Package Size	Dilution
04166	4 x 1 gallon / 3.78 L Containers	Ready-To-Use
5118737	1 x 5 gallon / 18.9 L Envirobox™/MC (TrailBlazer™/MC ready)	Ready-To-Use

Safety Reminder

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS are available on-line at www.diversey.com or by calling 888 352 2249.

Hazard Rating

HMIS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.