

Shiner ™/мс Spray Buff



Designed for use with traditional and ultra high speed spray buff procedures.

Effective

- Cleans and polishes
- Removes black heel marks

Easy to Use

- Designed for use with all Diversey floor finishes
- Use with rotary buffing machines on commercial floor finishes

Designed For

- Food Service
- Education
- Lodging

*

Use Overview

Shiner^{TMMC} **Spray Buff** is designed for use with traditional and ultra high speed spray buff procedures. Cleans and polishes floors to keep floor looking their best at all times. Use with rotary buffing machines on commercial floor finishes.

Traditional Spray Buffing

Note: Floors should have a minimum of two coats of floor finish prior to spray buffing.

- Prepare floor by dust mopping, damp mopping or autoscrubbing as required.
- Pour undiluted product into trigger spray bottle.
- Spray a fine mist on the floor. Do not over wet.
- Buff immediately with a spray buff machine and pad.
- For best results, flip or change pad frequently.

Spray Blazing (Ultra High Speed Spray Buffing)

Note: Floors should have a minimum of two coats of floor finish prior to spray blazing.

Damp mop or auto scrub floor.

Product Specifications

Description	
Color/Form	Opaque white, liquid
Flash Point	> 200° F (> 93.3° C)
рН	8.4
Scent	Characteristic
Shelf Life	2 years
Solubility	Insoluble
Specific Gravity	0.982

Hazard Rating

HMIS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.

Available items

Product Code	Description/Package Size	Dilution
54103	4 x 1 gallon / 3.78 L Containers	Ready-To-Use, 1:1

Safety Reminder

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS are available on-line at www.diversey.com or by calling 888 352 2249.



- Mix product with water at a 1:1 dilution in spray blazing bottle.
- > Attach a UHS rated pad to a UHS machine (min. speed 1500 rpm).
- Start burnisher and proceed at an average pace. Spray a fine mist on the floor every five steps (approx. 12–15 ft./4–5 m).
- For best results, flip or change pad frequently.

Note: Floors can be slippery when wet or contaminated with foreign materials. Promptly clean up spills and foreign materials.

