



PRODUCT TECHNICAL DATA SHEET

SW066 Spray Adhesive

DESCRIPTION: A high-performance product perfect for use in the art studio, graphic arts or screenprinting shop, or the sign shop. No. 66 is a non-wrinkling, repositionable, water-resistant, quick or long tack adhesive that provides either a temporary or permanent bond.

USES: This spray can be used to bond many materials including: metal, cardboard, foam rubber, plastic films, glass, wood, paper and cloth. Ideal for quick layouts, paste-ups, labeling and display assembly.

SPECS:	Can Size:	16 oz.
	Net Weight:	11 oz.
	Shipping Weight:	11 lbs.
	Packaged:	12 cans per case
	UPC Number:	0 41911 00066 6
PHYSICAL CHARACTERISTICS:	Color:	White
	Fragrance:	Solvent
	Shelf Life:	1 Year +
REGULATORY:	Recyclable Packaging:	Yes
	VOC Compliant CARB/OTC:	No
	CPSC Flame Extension:	Required to be labeled as extremely flammable per 16 CFR 1500
	24 HOUR MEDICAL EMERGENCY:	1-866-836-8855



- PRODUCT FEATURES:**
- Permanent or temporary bond
 - Non-wrinkling
 - Quick tack
 - Water resistant

AFTER USE: to clear valve of adhesive - hold can bottom up and spray a small amount. Spray tips may be cleaned with turpentine.

Manufactured by:
SPRAYWAY, INC.
 2651 Warrenville Rd. Ste. 300 • Downers Grove, IL 60515
 800-332-9000 • Fax: 630-543-7797 • www.spraywayinc.com